



# Thrust series : FM, F



## FM series with raceway

Bearing Reference e	Inner Ring Bore Dia.		Outer Ring Outer Dia.		Outer Ring Bore Dia.		Inner Ring Outer Dia.		Radius		Height		Load Rating		Max Speed (x1000rpm)		Cage Type	Ball Complement			Weight (Ref.) g
	d		D		d1		D1		rs(min)		H		Ca(N)	Coa(N)	Grease	Oil		Qty.: Z	Size:Dw		
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch							mm	inch	
F3-8M	3	0.1181	8	0.3150	3.2	0.1260	7.8	0.3071	0.15	0.0059	3.5	0.1378	993	590	19	28	TP	6	1.588	0.0625	0.9
F4-9M	4	0.1575	9	0.3543	4.2	0.1654	8.8	0.3465	0.15	0.0059	4.0	0.1575	944	640	17	25	TP	6	1.588	0.0625	1.2
F4-10M	4	0.1575	10	0.3937	4.2	0.1654	9.8	0.3858	0.15	0.0059	4.0	0.1575	925	661	16	24	TP	6	1.588	0.0625	1.5
F5-12M	5	0.1969	12	0.4724	5.2	0.2047	11.8	0.4646	0.20	0.0079	4.0	0.1575	1056	942	14	22	TP	8	1.588	0.0625	2.1
F6-12M	6	0.2362	12	0.4724	6.2	0.2441	11.8	0.4646	0.20	0.0079	4.5	0.1772	1819	1588	14	20	TP	9	2.000	0.0787	2.2
F6-14M	6	0.2362	14	0.5512	6.25	0.2461	13.8	0.5433	0.20	0.0079	5.0	0.1969	2155	1701	12	18	TP	7	2.381	0.0937	3.5
F7-13M	7	0.2756	13	0.5118	7.2	0.2835	16.8	0.6614	0.20	0.0079	4.5	0.1772	1767	1645	13	20	TP	9	2.000	0.0787	2.6
F7-17M	7	0.2756	17	0.6693	7.2	0.2835	16.8	0.6614	0.30	0.0118	6.0	0.2362	3086	2675	10	15	TP	8	2.778	0.1094	6.5
F8-16M	8	0.3150	16	0.6299	8.2	0.3228	15.8	0.6220	0.30	0.0118	5.0	0.1969	3917	3394	11	17	TP	9	3.000	0.1181	4.5
F8-19M	8	0.3150	19	0.7480	8.2	0.3228	18.8	0.7402	0.30	0.0118	7.0	0.2756	3939	3476	9	13	TP	8	3.175	0.1250	9.1
F9-20M	9	0.3543	20	0.7874	9.2	0.3622	19.8	0.7795	0.30	0.0118	7.0	0.2756	3855	3571	8	13	TP	8	3.175	0.1250	9.9
F10-18M	10	0.3937	18	0.7087	10.2	0.4016	17.8	0.7008	0.30	0.0118	5.5	0.2165	2470	2721	10	15	TP	10	2.381	0.0937	5.4

1) Bearings also available with stainless material : suffix H

## F series without raceway

Bearing Reference	Inner Ring Bore Dia.		Outer Ring Outer Dia.		Outer Ring Bore Dia.		Inner Ring Outer Dia.		Radius		Height		Load Rating		Cage Type	Ball Complement			Weight (Ref.) g
	d		D		d1		D1		rs(min)		H		Ca(N)	Coa(N)		Qty.: Z	Size:Dw		
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch					mm	inch	
F2-6	2.0	0.0787	6	0.2362	2.0	0.0787	6	0.2362	0.10	0.0039	3.0	0.1181	117	83	TD	6	1.000	0.0394	0.6
F2X-7	2.5	0.0984	7	0.2756	2.5	0.0984	7	0.2756	0.10	0.0039	3.5	0.1378	156	117	TD	6	1.200	0.0472	0.9
F3-8	3.0	0.1181	8	0.3150	3.0	0.1181	8	0.3150	0.10	0.0039	3.5	0.1378	166	137	TD	7	1.200	0.0472	0.6
F4-9	4.0	0.1575	9	0.3543	4.0	0.1575	9	0.3543	0.15	0.0059	4.0	0.1575	166	156	TD	8	1.200	0.0472	1.5
F4-10	4.0	0.1575	10	0.3937	4.0	0.1575	10	0.3937	0.15	0.0059	4.5	0.1772	274	245	TD	7	1.588	0.0625	2.0
F5-11	5.0	0.1969	11	0.4331	5.0	0.1969	11	0.4331	0.15	0.0059	4.5	0.1772	284	284	TD	7	1.588	0.0625	2.4
F6-12	6.0	0.2362	12	0.4724	6.0	0.2362	12	0.4724	0.15	0.0059	4.5	0.1772	274	284	TD	9	1.588	0.0625	2.5
F7-15	7.0	0.2756	15	0.5906	7.0	0.2756	15	0.5906	0.20	0.0079	5.0	0.1969	558	548	TD	8	2.381	0.0937	4.4
F8-16	8.0	0.3150	16	0.6299	8.0	0.3150	16	0.9299	0.20	0.0079	5.0	0.1969	597	627	TD	8	2.000	0.0787	5.0
F9-17	9.0	0.3543	17	0.6693	9.0	0.3543	17	0.6693	0.20	0.0079	5.0	0.1969	437	542	TD	9	2.000	0.0787	5.1
F10-18	10.0	0.3937	18	0.7087	10.0	0.3937	18	0.7087	0.20	0.0079	5.5	0.2165	617	705	TD	9	2.381	0.0937	6.0

1) Bearings also available with stainless material : suffix H (Cage material : Brass)